


姿図



品 番	DSL-4896YW
光 源	LDA4L-H-E17 <DAIKO>
定格光束	440 lm
1/2照度角	75°
ビーム角	116°

器具効率	60.6 %
上方光束	0.0 %
下方光束	60.6 %
器具間隔 最大限 (取付高さH)	A 1.54 H B 1.54 H
保 守 率	良 0.67 中 0.63 否 0.56

反射率 (%)	天井	80			70			50			30			0
	壁	50	30	10	50	30	10	50	30	10	50	30	10	0
	床	20			20			20			20			0
室指数		照 明 率 (× 0.01)												
0.6		29	24	21	29	24	21	28	23	20	27	23	20	19
0.8		35	30	27	35	30	26	34	29	26	33	29	26	25
1		41	35	32	40	35	32	39	34	31	38	34	31	29
1.25		45	41	37	45	40	37	43	39	36	42	38	36	34
1.5		49	44	41	48	44	41	47	43	40	45	42	39	37
2		54	50	47	53	50	47	51	48	46	50	47	45	43
2.5		58	54	51	56	53	51	54	52	49	52	50	48	46
3		60	57	54	59	56	53	57	54	52	55	53	51	48
4		63	60	58	62	59	57	59	57	55	57	55	54	51
5		65	62	60	63	61	59	61	59	58	58	57	56	53

