


姿図



品 番	DOL-4018YB
光 源	LED 15.2W 2700K
定格光束	1120.0 lm
1/2照度角	31°
ビーム角	32°

器具効率	100.0	%	反射率 (%)	天井	80			70			50			30			0
上方光束	0.0	%		壁	50	30	10	50	30	10	50	30	10	50	30	10	0
下方光束	100.0	%		床	20			20			20			20			0
			室指数	照 明 率 (× 0.01)													
			0.6	79	74	71	78	74	71	77	73	70	77	73	70	69	
器具間隔	A	0.55 H	0.8	85	80	76	84	79	76	83	79	76	82	78	75	73	
最大限			1	91	86	82	90	85	82	88	84	81	86	83	80	78	
(取付高さH)	B	0.55 H	1.25	95	91	87	94	90	87	92	88	86	90	87	85	82	
			1.5	99	94	91	97	93	90	95	92	89	93	90	88	85	
	良	0.69	2	104	100	97	103	99	97	100	97	95	97	95	93	90	
	中	0.67	2.5	108	105	102	106	103	101	103	101	99	100	98	97	93	
			3	110	108	105	108	106	104	105	103	102	102	101	99	96	
保 守 率			4	113	111	109	111	109	108	107	106	105	104	103	102	98	
	否	0.63	5	114	113	112	112	111	110	108	107	106	105	104	103	99	

