


姿図



| | |
|--------|---------------------|
| 品番 | DSY-5233NWE |
| 光源 | LED 7.6W 4000K |
| 定格光束 | 349 lm |
| 1/2照度角 | A-A' 64° B-B' 64° |
| ビーム角 | A-A' 110° B-B' 106° |

| | |
|------------------------|----------|
| 器具効率 | 100.0 % |
| 上方光束 | 2.1 % |
| 下方光束 | 97.9 % |
| 器具間隔 最大限 (取付高さH) | A 1.24 H |
| | B 1.24 H |
| 保守率 | 良 0.69 |
| | 中 0.67 |
| | 否 0.63 |

| 反射率 (%) | 天井 | | | 70 | | | 50 | | | 30 | | | 0 | |
|---------|------------------|-----|----|-----|----|----|----|----|----|----|----|----|----|---|
| | 壁 | 50 | 30 | 10 | 50 | 30 | 10 | 50 | 30 | 10 | 50 | 30 | 10 | 0 |
| | 床 | 20 | | | 20 | | | 20 | | | 20 | | | 0 |
| 室指数 | 照 明 率 (× 0.01) | | | | | | | | | | | | | |
| 0.6 | 46 | 38 | 32 | 45 | 37 | 32 | 44 | 37 | 32 | 43 | 36 | 31 | 29 | |
| 0.8 | 56 | 47 | 41 | 55 | 47 | 41 | 53 | 46 | 40 | 51 | 45 | 40 | 37 | |
| 1 | 64 | 55 | 49 | 63 | 55 | 49 | 61 | 53 | 48 | 58 | 52 | 47 | 44 | |
| 1.25 | 72 | 63 | 57 | 70 | 63 | 56 | 68 | 61 | 55 | 65 | 59 | 55 | 51 | |
| 1.5 | 78 | 70 | 63 | 76 | 69 | 63 | 73 | 67 | 61 | 70 | 65 | 60 | 57 | |
| 2 | 86 | 79 | 73 | 85 | 78 | 72 | 81 | 75 | 71 | 78 | 73 | 69 | 65 | |
| 2.5 | 92 | 86 | 80 | 90 | 84 | 79 | 86 | 81 | 77 | 83 | 79 | 75 | 71 | |
| 3 | 96 | 91 | 86 | 94 | 89 | 84 | 90 | 86 | 82 | 86 | 83 | 80 | 75 | |
| 4 | 101 | 97 | 92 | 99 | 95 | 91 | 95 | 91 | 88 | 91 | 88 | 85 | 80 | |
| 5 | 104 | 100 | 97 | 102 | 98 | 95 | 97 | 94 | 92 | 93 | 91 | 89 | 83 | |

A-A'

B-B'

