


姿図



品番	DEG-40211WE
光源	LED 1.9W 5000K
定格光束	1070.0 lm
保守率	0.92
備考	非常灯点灯時の照度(30分後)

非常灯配置表

器具取付高さ(m)	2.1	2.2	2.3	2.4	2.5	2.6	2.7	2.8	2.9	3.0	3.1	3.2	3.3	3.4	3.5	3.6	3.7	3.8	3.9	4.0	4.1	4.2	4.3	4.4	4.5	5.0	5.5	
単体配置	A1	5.3	5.5	5.6	5.7	5.9	6.0	6.1	6.2	6.3	6.4	6.5	6.6	6.7	6.8	6.9	7.0	7.1	7.2	7.3	7.4	7.5	7.6	7.6	7.7	7.8	8.0	6.8
直線配置	A2	11.8	12.1	12.5	12.9	13.2	13.5	14.0	14.3	14.6	15.0	15.3	15.6	15.8	16.1	16.4	16.5	16.8	17.1	17.3	17.5	17.7	18.0	18.2	18.4	18.6	19.5	20.5
四角配置	A4	9.2	9.6	9.9	10.2	10.5	10.8	11.2	11.4	11.7	12.0	12.3	12.5	12.8	13.1	13.3	13.6	13.8	14.1	14.3	14.5	14.8	15.0	15.2	15.4	15.6	16.6	17.4
壁からの距離(最大)	AO	3.7	3.9	4.0	4.0	4.1	4.2	4.3	4.4	4.5	4.6	4.6	4.7	4.8	4.8	4.8	4.9	4.9	4.9	5.0	5.0	5.0	5.1	5.0	5.1	5.1	5.3	5.4

器具取付高さ(m)	6.0	6.5	7.0	7.5	8.0	8.5	9.0																								
単体配置	A1	6.5	6.2	5.7	5.1	4.2	3.3	1.4																							
直線配置	A2	21.3	20.8	20.9	20.8	18.8	18.3	17.6																							
四角配置	A4	18.2	18.9	19.5	20.2	18.8	18.3	17.6																							
壁からの距離(最大)	AO	5.4	4.3	3.7	2.8	1.3	1.2	1.3																							

