


姿図



品番	DOL-4017YS
光源	LED 15W 2700K
定格光束	1120.0 lm
1/2照度角	31°
ビーム角	32°

器具効率	100.0 %
上方光束	0.0 %
下方光束	100.0 %
器具間隔 最大限 (取付高さH)	A 0.55 H
	B 0.55 H
保守率	良 0.69
	中 0.67
	否 0.63

反射率 (%)	天井			壁			50			30			0		
	80	70	50	50	30	10	50	30	10	50	30	10	50	30	10
床	20	20	20	20	20	20	20	20	20	20	20	20	20	20	20
室指数	照 明 率 ( × 0.01 )														
0.6	79	74	71	78	74	71	77	73	70	77	73	70	69	69	69
0.8	85	80	76	84	79	76	83	79	76	82	78	75	73	73	73
1	91	86	82	90	85	82	88	84	81	86	83	80	78	78	78
1.25	95	91	87	94	90	87	92	88	86	90	87	85	82	82	82
1.5	99	94	91	97	93	90	95	92	89	93	90	88	85	85	85
2	104	100	97	103	99	97	100	97	95	97	95	93	90	90	90
2.5	108	105	102	106	103	101	103	101	99	100	98	97	93	93	93
3	110	108	105	108	106	104	105	103	102	102	101	99	96	96	96
4	113	111	109	111	109	108	107	106	105	104	103	102	98	98	98
5	114	113	112	112	111	110	108	107	106	105	104	103	99	99	99

