


姿図



品 番

DDL-4763AW

光 源

LDA4WW-H-E17 <DAIKO>

定格光束

445.0 lm

1/2照度角

64°

ビーム角

106°

器具効率	79.1 %
上方光束	0.0 %
下方光束	79.0 %

器具間隔 最大限 (取付高さH)	A 1.24 H
	B 1.24 H

保 守 率	良	0.69
	中	0.67
	否	0.63

反射率 (%)	天井	80			70			50			30			0
	壁	50	30	10	50	30	10	50	30	10	50	30	10	0
	床	20			20			20			20			0
室指数		照 明 率 (× 0.01)												
0.6		39	32	28	38	32	28	37	31	28	36	31	27	26
0.8		47	40	36	46	40	36	45	39	35	44	39	35	33
1		54	47	43	53	47	42	51	46	42	50	45	41	39
1.25		60	54	49	59	53	49	57	52	48	56	51	48	46
1.5		65	59	55	64	58	54	62	57	53	60	56	52	50
2		72	67	62	70	66	62	68	64	61	66	62	59	57
2.5		76	71	68	74	70	67	72	68	65	69	66	64	61
3		79	75	72	77	74	71	75	72	69	72	69	67	64
4		82	79	76	81	78	75	78	75	73	75	73	71	68
5		85	82	79	83	80	78	80	78	76	77	75	73	70

