


姿図



品番	DSL-4895YW
光源	LDA4L-H-E17 <DAIKO>
定格光束	440 lm
1/2照度角	75°
ビーム角	116°

器具効率	60.6 %
上方光束	0.0 %
下方光束	60.6 %
器具間隔 最大限 (取付高さH)	A 1.54 H
	B 1.54 H
保守率	良 0.67
	中 0.63
	否 0.56

反射率 (%)	天井	80			70			50			30			0
	壁	50	30	10	50	30	10	50	30	10	50	30	10	0
	床	20			20			20			20			0
室指数	照 明 率 (× 0.01)													
0.6	29	24	21	29	24	21	28	23	20	27	23	20	19	
0.8	35	30	27	35	30	26	34	29	26	33	29	26	25	
1	41	35	32	40	35	32	39	34	31	38	34	31	29	
1.25	45	41	37	45	40	37	43	39	36	42	38	36	34	
1.5	49	44	41	48	44	41	47	43	40	45	42	39	37	
2	54	50	47	53	50	47	51	48	46	50	47	45	43	
2.5	58	54	51	56	53	51	54	52	49	52	50	48	46	
3	60	57	54	59	56	53	57	54	52	55	53	51	48	
4	63	60	58	62	59	57	59	57	55	57	55	54	51	
5	65	62	60	63	61	59	61	59	58	58	57	56	53	

