


姿図



品 番	DOL-4020YB
光 源	LED 15W 2700K
定格光束	1120.0 lm
1/2照度角	31°
ビーム角	32°

器具効率	100.0 %
上方光束	0.0 %
下方光束	100.0 %
器具間隔 最大限 (取付高さH)	A 0.55 H B 0.55 H
保 守 率	良 0.69 中 0.67 否 0.63

反射率 (%)	天井	80			70			50			30			0
	壁	50	30	10	50	30	10	50	30	10	50	30	10	0
	床	20			20			20			20			0
室指数		照 明 率 (× 0.01)												
0.6		79	74	71	78	74	71	77	73	70	77	73	70	69
0.8		85	80	76	84	79	76	83	79	76	82	78	75	73
1		91	86	82	90	85	82	88	84	81	86	83	80	78
1.25		95	91	87	94	90	87	92	88	86	90	87	85	82
1.5		99	94	91	97	93	90	95	92	89	93	90	88	85
2		104	100	97	103	99	97	100	97	95	97	95	93	90
2.5		108	105	102	106	103	101	103	101	99	100	98	97	93
3		110	108	105	108	106	104	105	103	102	102	101	99	96
4		113	111	109	111	109	108	107	106	105	104	103	102	98
5		114	113	112	112	111	110	108	107	106	105	104	103	99

