



品番	DSY-4429AWG
光源	LED 37W 3500K
定格光束	4500 lm
1/2照度角	A-A' 65° B-B' 63°
ビーム角	A-A' 114° B-B' 106°

器具効率	100.0 %
上方光束	8.2 %
下方光束	91.8 %
器具間隔 最大限 (取付高さH)	A 1.27 H B 1.23 H
保守率	良 0.69 中 0.67 否 0.63

反射率 (%)	天井				70			50			30			0
	壁	50	30	10	50	30	10	50	30	10	50	30	10	0
	床				20			20			20			0
室指数	照 明 率 (× 0.01)													
0.6	45	36	31	44	36	30	42	35	30	40	34	29	27	
0.8	54	46	39	53	45	39	51	43	38	48	42	37	34	
1	62	54	47	61	53	47	58	51	45	55	49	44	41	
1.25	70	62	55	68	60	54	65	58	53	61	56	51	47	
1.5	76	68	61	74	66	60	70	64	58	66	61	56	52	
2	84	77	71	82	75	70	78	72	67	73	69	65	60	
2.5	90	83	78	87	81	76	83	78	73	78	74	71	65	
3	94	88	83	91	86	81	86	82	78	82	78	75	69	
4	99	94	90	96	92	88	91	87	84	86	83	80	74	
5	102	98	94	99	96	92	94	91	88	88	86	84	77	

