


姿図



品 番	DBK-39749Y
光 源	LDA5L-G/40W/B27K <DAIKO>
定格光束	500 lm
1/2照度角	67°
ビーム角	110°

器具効率	46.4	%	反射率 (%)	天井	80			70			50			30			0
上方光束	0.0	%		壁	50	30	10	50	30	10	50	30	10	50	30	10	0
下方光束	46.4	%		床	20			20			20			20			0
				室指数	照 明 率 (× 0.01)												
器具間隔 最大限 (取付高さH)	A	1.32	H	0.6	22	18	16	22	18	16	21	18	16	21	18	16	15
	B	1.32	H	0.8	27	23	20	27	23	20	26	22	20	25	22	20	19
				1	31	27	24	30	27	24	29	26	24	28	26	23	22
				1.25	35	31	28	34	30	28	33	30	27	32	29	27	26
保 守 率	良 中 否	0.67 0.63 0.56	1.5	37	34	31	37	33	31	35	32	30	34	32	30	28	
			2	41	38	36	41	38	35	39	37	35	38	36	34	32	
			2.5	44	41	39	43	41	38	41	39	37	40	38	37	35	
			3	46	43	41	45	43	41	43	41	40	42	40	39	37	
			4	48	46	44	47	45	44	45	44	42	43	42	41	39	
			5	49	48	46	48	47	45	46	45	44	45	44	43	41	

