


姿図



品 番	DSL-4705AW
光 源	LED 9.1W 3500K
定格光束	920.0 lm
1/2照度角	65°
ビーム角	90°

器具効率	100.0 %
上方光束	11.8 %
下方光束	88.2 %
器具間隔 最大限 (取付高さH)	A 1.28 H B 1.28 H
保 守 率	良 0.67 中 0.63 否 0.56

反射率 (%)	天井	80			70			50			30			0
	壁	50	30	10	50	30	10	50	30	10	50	30	10	0
	床	20			20			20			20			0
室指数		照 明 率 (× 0.01)												
0.6		49	41	36	48	41	36	46	39	35	44	38	34	31
0.8		58	50	44	57	49	43	54	47	42	51	45	41	38
1		65	57	51	64	56	50	60	54	49	57	52	47	44
1.25		72	64	58	70	63	57	66	60	55	63	58	53	49
1.5		78	70	64	75	68	63	71	65	60	67	62	58	53
2		85	79	73	83	77	71	78	73	68	73	69	65	60
2.5		91	84	79	88	82	77	82	78	74	77	74	70	64
3		94	89	84	91	86	82	86	81	78	80	77	74	68
4		99	94	90	96	91	88	89	86	83	84	81	79	72
5		102	98	94	98	95	91	92	89	86	86	84	82	74

