


姿図



| | |
|--------|--------------------------|
| 品番 | LZW-93426XS+LZA-93164NSW |
| 光源 | DECO-S35C 4.3W 4000K W |
| 定格光束 | 500 lm |
| 1/2照度角 | 30° |
| ビーム角 | 32° |

| | |
|------------------------|---------------|
| 器具効率 | 87.2 % |
| 上方光束 | 0.0 % |
| 下方光束 | 87.2 % |
| 器具間隔 最大限 (取付高さH) | A 0.54 H B |
| 保守率 | 良 0.67 |
| | 中 0.63 |
| | 否 0.56 |

| 反射率 (%) | 天井 | 80 | | | 70 | | | 50 | | | 30 | | | 0 |
|---------|------------------|----|----|----|----|----|----|----|----|----|----|----|----|---|
| | 壁 | 50 | 30 | 10 | 50 | 30 | 10 | 50 | 30 | 10 | 50 | 30 | 10 | 0 |
| | 床 | 20 | | | 20 | | | 20 | | | 20 | | | 0 |
| 室指数 | 照 明 率 (× 0.01) | | | | | | | | | | | | | |
| 0.6 | 70 | 66 | 63 | 70 | 66 | 63 | 69 | 66 | 63 | 68 | 65 | 63 | 62 | |
| 0.8 | 75 | 71 | 68 | 75 | 71 | 68 | 74 | 70 | 68 | 73 | 70 | 67 | 66 | |
| 1 | 80 | 76 | 73 | 80 | 76 | 73 | 78 | 75 | 72 | 77 | 74 | 72 | 70 | |
| 1.25 | 84 | 80 | 78 | 83 | 80 | 77 | 82 | 79 | 76 | 80 | 77 | 75 | 73 | |
| 1.5 | 87 | 84 | 81 | 86 | 83 | 80 | 84 | 81 | 79 | 82 | 80 | 78 | 76 | |
| 2 | 92 | 89 | 86 | 90 | 88 | 85 | 88 | 86 | 84 | 86 | 84 | 82 | 80 | |
| 2.5 | 95 | 92 | 90 | 93 | 91 | 89 | 90 | 89 | 87 | 88 | 87 | 85 | 82 | |
| 3 | 97 | 95 | 93 | 95 | 93 | 92 | 92 | 91 | 90 | 90 | 89 | 88 | 84 | |
| 4 | 99 | 97 | 96 | 97 | 96 | 95 | 94 | 93 | 92 | 91 | 90 | 89 | 86 | |
| 5 | 100 | 99 | 98 | 98 | 97 | 96 | 95 | 94 | 93 | 92 | 91 | 91 | 87 | |

