

姿図



品番	LLD-7141LUM3
光源	LED 25.0W 2700K
定格光束	640 lm
1/2照度角	15°
ビーム角	15°

器具効率	100.0 %
上方光束	0.0 %
下方光束	100.0 %
器具間隔 最大限 (取付高さH)	A 0.26 H
	B 0.26 H
保守率	良 0.67
	中 0.63
	否 0.56

反射率 (%)	天井	80			70			50			30			0
	壁	50	30	10	50	30	10	50	30	10	50	30	10	0
	床	20			20			20			20			0
室指数	照 明 率 (× 0.01)													
0.6	85	80	77	84	80	77	83	80	77	83	79	77	75	
0.8	90	86	83	90	85	82	88	85	82	87	84	81	80	
1	96	91	88	95	91	88	93	90	87	92	89	86	84	
1.25	100	96	93	99	95	92	97	94	91	95	92	90	88	
1.5	103	99	96	102	98	95	100	97	94	97	95	93	90	
2	108	105	102	107	104	101	104	101	99	101	99	98	95	
2.5	111	109	106	110	107	105	107	105	103	104	102	101	97	
3	114	112	110	112	110	108	109	107	106	106	104	103	100	
4	116	115	113	114	113	112	111	109	108	107	106	106	101	
5	118	117	115	116	115	114	112	111	110	108	107	107	102	

