


姿図



品番	LLD-7060YUM4+LZA-92128
光源	LED 13.7W 3000K
定格光束	260 lm
1/2照度角	25°
ビーム角	27°

器具効率	100.0 %
上方光束	0.0 %
下方光束	100.0 %
器具間隔 最大限 (取付高さH)	A 0.44 H B 0.45 H
保守率	良 0.67
	中 0.63
	否 0.56

反射率 (%)	天井	80			70			50			30			0
	壁	50	30	10	50	30	10	50	30	10	50	30	10	0
	床	20			20			20			20			0
室指数	照 明 率 (× 0.01)													
0.6	83	79	76	83	78	75	82	78	75	81	77	75	74	
0.8	89	84	81	88	84	80	87	83	80	85	82	79	78	
1	94	89	86	93	89	86	91	88	85	90	87	84	82	
1.25	98	94	91	97	93	90	95	92	89	93	90	88	86	
1.5	101	97	94	100	96	93	98	95	92	95	93	91	88	
2	106	103	100	105	102	99	102	99	97	99	97	96	93	
2.5	109	107	104	108	105	103	105	103	101	102	100	99	96	
3	112	110	108	110	108	106	107	105	104	104	103	101	98	
4	114	113	111	112	111	110	109	108	106	105	104	104	99	
5	116	115	113	114	113	112	110	109	108	106	106	105	100	

