


姿図



品 番	LLD-7140AUB5
光 源	LED 23.6W 3500K
定格光束	1040 lm
1/2照度角	41°
ビーム角	50°

器具効率	100.0 %
上方光束	0.0 %
下方光束	100.0 %
器具間隔 最大限 (取付高さH)	A 0.75 H B
保 守 率	良 0.67 中 0.63 否 0.56

反射率 (%)	天井	80			70			50			30			0
	壁	50	30	10	50	30	10	50	30	10	50	30	10	0
	床	20			20			20			20			0
室指数		照 明 率 (× 0.01)												
0.6		81	76	73	80	76	73	79	75	73	79	75	72	71
0.8		87	82	79	86	82	78	85	81	78	84	80	77	76
1		93	88	85	92	87	84	90	86	83	88	85	83	81
1.25		97	93	89	96	92	89	94	91	88	92	89	87	85
1.5		100	96	93	99	95	92	97	94	91	95	92	90	87
2		105	102	99	104	101	98	101	99	97	99	97	95	92
2.5		109	106	104	107	105	103	104	102	100	101	100	98	95
3		111	109	107	109	107	106	106	105	103	103	102	101	97
4		114	112	110	112	110	109	108	107	106	105	104	103	99
5		115	114	113	113	112	111	109	108	107	106	105	104	100

