


姿図



品 番	LLD-7061NUM4
光 源	LED 39W 4000K
定格光束	2200 lm
1/2照度角	19°
ビーム角	19°

器具効率	100.0 %
上方光束	0.0 %
下方光束	100.0 %
器具間隔 最大限 (取付高さH)	A 0.33 H B 0.33 H
保 守 率	良 0.67 中 0.63 否 0.56

反射率 (%)	天井	80			70			50			30			0
	壁	50	30	10	50	30	10	50	30	10	50	30	10	0
	床	20			20			20			20			0
室指数		照 明 率 (× 0.01)												
0.6		84	80	77	84	80	77	83	79	76	82	79	76	75
0.8		90	85	82	89	85	82	88	84	81	87	83	81	79
1		95	91	87	94	90	87	93	89	86	91	88	86	84
1.25		99	95	92	98	94	91	96	93	90	94	92	89	87
1.5		102	98	95	101	98	95	99	96	93	97	94	92	90
2		107	104	101	106	103	100	103	101	99	100	99	97	94
2.5		111	108	106	109	107	105	106	104	102	103	101	100	97
3		113	111	109	111	109	108	108	106	105	105	104	103	99
4		115	114	112	113	112	111	110	109	108	106	105	105	100
5		117	116	114	115	114	113	111	110	109	107	107	106	101

