


姿図



品 番	DDL-4245FB
光 源	LED 6.7W 2700K-5000K
定格光束	470 lm
1/2照度角	63°
ビーム角	90°

器具効率	100.0 %
上方光束	0.0 %
下方光束	100.0 %
器具間隔 最大限 (取付高さH)	A 1.23 H B 1.23 H
保 守 率	良 0.67 中 0.63 否 0.56

反射率 (%)	天井	80			70			50			30			0
	壁	50	30	10	50	30	10	50	30	10	50	30	10	0
	床	20			20			20			20			0
室指数		照 明 率 (× 0.01)												
0.6		57	50	45	56	49	45	55	49	44	54	48	44	42
0.8		67	60	54	66	59	54	65	58	54	63	58	53	51
1		75	68	63	74	68	63	72	66	62	71	65	61	59
1.25		83	76	71	82	75	70	79	74	70	77	72	69	66
1.5		88	82	77	87	81	76	84	79	75	82	78	74	71
2		96	90	86	94	89	85	91	87	83	88	85	82	79
2.5		100	96	92	99	94	91	95	92	89	92	89	87	83
3		104	100	96	102	98	95	98	95	92	95	92	90	86
4		107	104	101	105	102	99	101	99	97	98	96	94	90
5		109	107	104	107	105	102	103	101	99	99	98	96	92

