


姿図



品 番	LLD-7140YUB4
光 源	LED 23.6W 3000K
定格光束	1010 lm
1/2照度角	41°
ビーム角	50°

器具効率	100.0 %
上方光束	0.0 %
下方光束	100.0 %
器具間隔 最大限 (取付高さ H)	A 0.75 H B
保 守 率	良 0.67 中 0.63 否 0.56

反射率 (%)	天井	80			70			50			30			0
	壁	50	30	10	50	30	10	50	30	10	50	30	10	0
	床	20			20			20			20			0
室指数	照 明 率 (× 0.01)													
0.6	81	76	73	80	76	73	79	75	73	79	75	72	71	
0.8	87	82	79	86	82	78	85	81	78	84	80	77	76	
1	93	88	85	92	87	84	90	86	83	88	85	83	81	
1.25	97	93	89	96	92	89	94	91	88	92	89	87	85	
1.5	100	96	93	99	95	92	97	94	91	95	92	90	87	
2	105	102	99	104	101	98	101	99	97	99	97	95	92	
2.5	109	106	104	107	105	103	104	102	100	101	100	98	95	
3	111	109	107	109	107	106	106	105	103	103	102	101	97	
4	114	112	110	112	110	109	108	107	106	105	104	103	99	
5	115	114	113	113	112	111	109	108	107	106	105	104	100	

