


姿図



品番	LLD-7141YUM5+LZA-92952
光源	LED 25.0W 3000K
定格光束	540 lm
1/2照度角	14°
ビーム角	15°

器具効率	100.0 %
上方光束	0.0 %
下方光束	100.0 %
器具間隔 最大限 (取付高さH)	A 0.25 H B 0.25 H
保守率	良 0.67
	中 0.63
	否 0.56

反射率 (%)	天井	80			70			50			30			0
	壁	50	30	10	50	30	10	50	30	10	50	30	10	0
床	20			20			20			20			0	
室指数	照 明 率 (× 0.01)													
0.6	85	80	77	84	80	77	83	80	77	82	79	77	75	
0.8	90	86	82	90	85	82	88	84	82	87	84	81	79	
1	96	91	88	95	91	88	93	90	87	92	88	86	84	
1.25	100	96	92	99	95	92	97	93	91	95	92	90	88	
1.5	103	99	96	102	98	95	99	96	94	97	95	93	90	
2	108	105	102	107	104	101	104	101	99	101	99	97	94	
2.5	111	109	106	110	107	105	107	105	103	104	102	101	97	
3	114	112	110	112	110	108	109	107	106	105	104	103	99	
4	116	115	113	114	113	111	110	109	108	107	106	105	101	
5	118	116	115	116	114	113	112	111	110	108	107	107	102	

