


姿図



品番	LZD-9030FWB4
光源	LED 29W 5000K
定格光束	2450 lm
1/2照度角	60°
ビーム角	66°

器具効率	100.0 %
上方光束	0.0 %
下方光束	100.0 %
器具間隔 最大限 (取付高さH)	A 1.15 H B
保守率	良 0.67
	中 0.63
	否 0.56

反射率 (%)	天井	80			70			50			30			0
	壁	50	30	10	50	30	10	50	30	10	50	30	10	0
	床	20			20			20			20			0
室指数	照 明 率 ( × 0.01 )													
0.6	71	65	62	71	65	61	70	65	61	69	64	61	59	
0.8	79	73	69	78	73	69	77	72	68	76	71	68	66	
1	86	80	76	85	80	76	83	79	75	81	77	74	72	
1.25	91	86	82	90	85	82	88	84	81	86	83	80	77	
1.5	96	91	87	94	90	86	92	88	85	90	86	84	81	
2	102	97	94	100	96	93	97	94	92	95	92	90	87	
2.5	105	102	99	104	101	98	101	98	96	98	96	94	90	
3	108	105	103	106	104	101	103	101	99	100	98	97	93	
4	111	109	106	109	107	105	105	104	102	102	100	99	95	
5	113	111	109	111	109	107	107	105	104	103	102	101	96	

