


姿図



品 番	LZD-93509LB+LZA-90815E
光 源	LED 24W 2700K
定格光束	2110 lm
1/2照度角	40°
ビーム角	44°

器具効率	100.0 %
上方光束	0.0 %
下方光束	100.0 %
器具間隔 最大限 (取付高さH)	A 0.73 H B
保 守 率	良 0.67 中 0.63 否 0.56

反射率 (%)	天井	80			70			50			30			0
	壁	50	30	10	50	30	10	50	30	10	50	30	10	0
	床	20			20			20			20			0
室指数		照 明 率 (× 0.01)												
0.6		75	70	66	74	69	66	73	69	66	72	68	65	64
0.8		82	77	73	81	76	73	80	76	72	79	75	72	70
1		89	83	80	88	83	79	86	82	78	84	81	78	76
1.25		94	89	85	93	88	85	91	87	84	89	85	83	80
1.5		98	93	90	96	92	89	94	90	88	92	89	86	84
2		103	100	96	102	98	96	99	96	94	96	94	92	89
2.5		107	104	101	105	102	100	102	100	98	99	97	96	92
3		110	107	105	108	105	103	104	103	101	101	100	98	95
4		112	110	108	110	108	107	107	105	104	103	102	101	97
5		114	112	111	112	110	109	108	107	106	104	103	102	98

