


姿図



品番	LXD-93108AWNE+LZA-92809
光源	LED 12.2W 3500K
定格光束	170 lm
1/2照度角	13°
ビーム角	13°

器具効率	100.0 %
上方光束	0.0 %
下方光束	100.0 %
器具間隔 最大限 (取付高さH)	A 0.23 H B
保守率	良 0.67
	中 0.63
	否 0.56

反射率 (%)	天井	80			70			50			30			0
	壁	50	30	10	50	30	10	50	30	10	50	30	10	0
	床	20			20			20			20			0
室指数	照 明 率 (× 0.01)													
0.6	85	81	77	85	80	77	84	80	77	83	79	77	76	
0.8	91	86	83	90	86	82	89	85	82	87	84	81	80	
1	96	92	88	95	91	88	93	90	87	92	89	86	84	
1.25	100	96	93	99	95	92	97	94	91	95	92	90	88	
1.5	103	99	96	102	99	96	100	97	94	98	95	93	90	
2	108	105	102	107	104	101	104	102	100	101	100	98	95	
2.5	112	109	107	110	108	106	107	105	103	104	102	101	98	
3	114	112	110	112	110	109	109	107	106	106	105	104	100	
4	117	115	113	115	113	112	111	110	109	107	107	106	101	
5	118	117	116	116	115	114	112	111	110	108	108	107	102	

