


姿図



品番	DDL-6104WW
光源	LED 6.8W 5000K
定格光束	780 lm
1/2照度角	62°
ビーム角	94°

器具効率	100.0 %
上方光束	0.0 %
下方光束	100.0 %
器具間隔 最大限 (取付高さH)	A 1.21 H B 1.21 H
保守率	良 0.67
	中 0.63
	否 0.56

反射率 (%)	天井			壁			50			30			0		
	80	70	50	50	30	10	50	30	10	50	30	10	50	30	10
床	20			20			20			20			0		
室指数	照 明 率 (× 0.01)														
0.6	54	47	42	54	47	42	52	46	41	51	45	41	39		
0.8	65	57	52	64	57	52	63	56	51	61	55	51	49		
1	74	66	61	73	66	60	71	64	60	69	63	59	57		
1.25	81	74	69	80	74	69	78	72	68	76	71	67	64		
1.5	87	80	75	85	79	75	83	78	74	80	76	72	70		
2	95	89	85	93	88	84	90	86	82	87	84	81	77		
2.5	99	95	91	98	93	90	94	91	88	91	88	86	82		
3	103	99	95	101	97	94	97	94	91	94	92	89	85		
4	107	103	100	105	101	99	101	98	96	97	95	93	89		
5	109	106	103	107	104	102	103	100	98	99	97	95	91		

