


姿図



品番	DSY-5464AW
光源	LED 6.6W 3500K
定格光束	690 lm
1/2照度角	A-A' 66° B-B' 64°
ビーム角	A-A' 110° B-B' 104°

器具効率	100.0 %
上方光束	4.3 %
下方光束	95.8 %
器具間隔 最大限 (取付高さH)	A 1.29 H
	B 1.26 H
保守率	良 0.69
	中 0.67
	否 0.63

反射率 (%)	天井	80			70			50			30			0
		壁	50	30	10	50	30	10	50	30	10	50	30	10
床		20			20			20			20			0
室指数		照 明 率 ( × 0.01 )												
0.6		46	38	32	45	38	32	44	37	32	42	36	31	29
0.8		56	47	41	55	47	41	53	46	40	51	45	40	37
1		64	56	49	63	55	49	60	53	48	58	52	47	44
1.25		72	63	57	70	62	56	67	61	55	64	59	54	51
1.5		78	70	63	76	68	63	73	66	61	69	64	60	56
2		86	79	73	84	78	72	80	75	70	77	72	68	64
2.5		92	85	80	90	84	79	85	80	76	81	77	74	69
3		96	90	85	93	88	84	89	85	81	85	81	78	73
4		101	96	92	98	94	90	93	90	87	89	86	84	78
5		104	100	96	101	98	94	96	93	90	92	89	87	81

A-A'

B-B'

