


姿図



| | |
|--------|------------------------|
| 品番 | LZD-91952YWE+LZA-93015 |
| 光源 | LED 28W 3000K |
| 定格光束 | 3110 lm |
| 1/2照度角 | 30° |
| ビーム角 | 31° |

| | |
|------------------------|---------------|
| 器具効率 | 100.0 % |
| 上方光束 | 0.0 % |
| 下方光束 | 100.0 % |
| 器具間隔 最大限 (取付高さH) | A 0.54 H B |
| 保守率 | 良 0.67 |
| | 中 0.63 |
| | 否 0.56 |

| 反射率 (%) | 天井 | 80 | | | 70 | | | 50 | | | 30 | | | 0 |
|---------|------------------|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|---|
| | 壁 | 50 | 30 | 10 | 50 | 30 | 10 | 50 | 30 | 10 | 50 | 30 | 10 | 0 |
| 床 | 20 | | | 20 | | | 20 | | | 20 | | | 0 | |
| 室指数 | 照 明 率 (× 0.01) | | | | | | | | | | | | | |
| 0.6 | 81 | 77 | 74 | 81 | 77 | 74 | 80 | 76 | 73 | 79 | 76 | 73 | 72 | |
| 0.8 | 87 | 83 | 79 | 87 | 82 | 79 | 85 | 81 | 78 | 84 | 81 | 78 | 76 | |
| 1 | 93 | 88 | 85 | 92 | 88 | 85 | 90 | 87 | 84 | 89 | 86 | 83 | 81 | |
| 1.25 | 97 | 93 | 90 | 96 | 92 | 89 | 94 | 91 | 88 | 92 | 90 | 87 | 85 | |
| 1.5 | 101 | 97 | 94 | 100 | 96 | 93 | 97 | 94 | 92 | 95 | 92 | 90 | 88 | |
| 2 | 106 | 103 | 100 | 104 | 101 | 99 | 102 | 99 | 97 | 99 | 97 | 95 | 92 | |
| 2.5 | 109 | 107 | 104 | 108 | 105 | 103 | 105 | 103 | 101 | 102 | 100 | 99 | 95 | |
| 3 | 112 | 110 | 108 | 110 | 108 | 106 | 107 | 105 | 104 | 104 | 102 | 101 | 97 | |
| 4 | 114 | 113 | 111 | 112 | 111 | 109 | 109 | 107 | 106 | 105 | 104 | 103 | 99 | |
| 5 | 116 | 114 | 113 | 114 | 113 | 111 | 110 | 109 | 108 | 106 | 105 | 105 | 100 | |

