


姿図



品 番

DSL-5493YBG

光 源

LED 6.2W 2700K

定格光束

265 lm

1/2照度角

12°

ビーム角

12°

器具効率	100.0 %
上方光束	0.0 %
下方光束	100.0 %
器具間隔 最大限 (取付高さH)	A 0.21 H B
保 守 率	良 0.67 中 0.63 否 0.56

反射率 (%)	天井	80			70			50			30			0
	壁	50	30	10	50	30	10	50	30	10	50	30	10	0
	床	20			20			20			20			0
室指数		照 明 率 (× 0.01)												
0.6		83	79	76	83	78	75	82	78	75	81	77	75	74
0.8		89	84	81	88	84	81	87	83	80	86	82	80	78
1		95	90	87	94	90	86	92	88	86	91	87	85	83
1.25		99	95	91	98	94	91	96	93	90	94	91	89	87
1.5		102	98	95	101	97	94	99	96	93	97	94	92	89
2		108	104	101	106	103	100	103	101	99	101	99	97	94
2.5		111	108	106	109	107	105	106	104	102	103	102	100	97
3		113	111	109	112	110	108	108	107	105	105	104	103	99
4		116	114	113	114	112	111	110	109	108	107	106	105	101
5		117	116	115	115	114	113	111	110	110	108	107	106	102

