


姿図



品番	LZD-91951NWE+LZA-93015
光源	LED 28W 4000K
定格光束	3100 lm
1/2照度角	15°
ビーム角	15°

器具効率	100.0 %
上方光束	0.0 %
下方光束	100.0 %
器具間隔 最大限 (取付高さH)	A 0.26 H B 0.26 H
保守率	良 0.67
	中 0.63
	否 0.56

反射率 (%)	天井	80			70			50			30			0
	壁	50	30	10	50	30	10	50	30	10	50	30	10	0
	床	20			20			20			20			0
室指数	照 明 率 ( × 0.01 )													
0.6	80	75	72	80	75	72	79	75	72	78	74	71	70	
0.8	87	81	78	86	81	78	84	80	77	83	79	77	75	
1	92	87	84	91	87	83	90	86	83	88	85	82	80	
1.25	97	92	89	96	92	88	94	90	87	92	89	86	84	
1.5	101	96	93	99	95	92	97	94	91	95	92	90	87	
2	106	102	99	104	101	98	102	99	97	99	97	95	92	
2.5	109	106	104	108	105	103	105	102	101	102	100	98	95	
3	112	110	107	110	108	106	107	105	103	104	102	101	97	
4	115	113	111	113	111	109	109	108	106	105	104	103	99	
5	116	115	113	114	113	112	110	109	108	106	106	105	100	

