


姿図



品番	DDL-6104AS
光源	LED 6.8W 3500K
定格光束	680 lm
1/2照度角	62°
ビーム角	94°

器具効率	100.0 %
上方光束	0.0 %
下方光束	100.0 %
器具間隔 最大限 (取付高さH)	A 1.21 H B 1.21 H
保守率	良 0.67
	中 0.63
	否 0.56

反射率 (%)	天井			壁			床			照明率 (×0.01)			
	80	70	50	30	10	50	30	10	50	30	10	0	
室指数	54	47	42	54	47	42	52	46	41	51	45	41	39
0.6	65	57	52	64	57	52	63	56	51	61	55	51	49
0.8	74	66	61	73	66	60	71	64	60	69	63	59	57
1	81	74	69	80	74	69	78	72	68	76	71	67	64
1.25	87	80	75	85	79	75	83	78	74	80	76	72	70
1.5	95	89	85	93	88	84	90	86	82	87	84	81	77
2	99	95	91	98	93	90	94	91	88	91	88	86	82
2.5	103	99	95	101	97	94	97	94	91	94	92	89	85
3	107	103	100	105	101	99	101	98	96	97	95	93	89
4	109	106	103	107	104	102	103	100	98	99	97	95	91
5													

