


姿図



品番	DSL-5345YWE
光源	LED 5.6W 2700K
定格光束	430 lm
1/2照度角	29°
ビーム角	32°

器具効率	100.0 %
上方光束	0.0 %
下方光束	100.0 %
器具間隔 最大限 (取付高さH)	A 0.52 H B 0.52 H
保守率	良 0.67
	中 0.63
	否 0.56

反射率 (%)	天井				70			50			30			0
	壁	50	30	10	50	30	10	50	30	10	50	30	10	0
	床				20			20			20			0
室指数	照 明 率 ( × 0.01 )													
0.6	78	73	69	77	72	69	76	72	69	75	71	69	67	
0.8	84	79	75	84	79	75	82	78	75	81	77	74	73	
1	90	85	82	89	85	81	88	84	81	86	83	80	78	
1.25	95	90	87	94	90	86	92	88	85	90	87	84	82	
1.5	99	94	91	97	93	90	95	92	89	93	90	88	85	
2	104	100	97	103	99	97	100	97	95	97	95	93	90	
2.5	108	105	102	106	103	101	103	101	99	100	98	97	93	
3	110	108	106	109	106	104	105	103	102	102	101	99	96	
4	113	111	109	111	109	108	107	106	105	104	103	102	98	
5	115	113	111	112	111	110	108	107	106	105	104	103	99	

