


姿図



品番	DBK-40036A
光源	LED 4.6W 3500K
定格光束	480 lm
1/2照度角	(A57° A' 31°) B-B' 81°
ビーム角	(A180° A' 52°) B-B' 360°

器具効率	100.0 %
上方光束	50.0 %
下方光束	50.0 %
器具間隔 最大限 (取付高さH)	A *** H B 1.70 H
保守率	良 0.63
	中 0.60
	否 0.56

反射率 (%)	天井				70			50			30			0
	壁	50	30	10	50	30	10	50	30	10	50	30	10	0
	床				20			20			20			0
室指数	照 明 率 (× 0.01)													
0.6	34	25	20	31	23	18	26	20	15	21	16	12	7	
0.8	42	33	27	39	31	25	32	26	21	26	21	17	10	
1	49	40	33	45	37	30	37	31	26	30	25	21	13	
1.25	56	47	40	51	43	37	42	36	31	34	29	25	16	
1.5	61	52	45	56	48	42	46	40	35	37	33	29	18	
2	69	61	54	63	56	50	52	47	42	42	38	34	22	
2.5	75	67	60	68	62	56	57	51	47	46	42	39	26	
3	79	72	65	72	66	60	60	55	51	49	45	42	28	
4	84	78	73	77	72	67	64	60	56	52	49	46	31	
5	88	82	77	81	76	71	67	63	60	55	52	49	34	

