


姿図



品番	DSL-4719FBG
光源	LED 8W 5000K-2700K
定格光束	325 lm
1/2照度角	62°
ビーム角	88°

器具効率	100.0 %
上方光束	0.0 %
下方光束	100.0 %
器具間隔 最大限 (取付高さH)	A 1.20 H B 1.20 H
保守率	良 0.67
	中 0.63
	否 0.56

反射率 (%)	天井	80			70			50			30			0
	壁	50	30	10	50	30	10	50	30	10	50	30	10	0
	床	20			20			20			20			0
室指数	照 明 率 (× 0.01)													
0.6	59	52	47	58	52	47	57	51	47	56	51	47	45	
0.8	70	63	58	69	62	57	67	61	57	66	61	57	55	
1	78	71	66	77	71	66	75	70	65	73	69	65	63	
1.25	85	79	74	84	78	74	82	77	73	80	76	72	70	
1.5	91	85	80	89	84	80	87	82	78	84	81	77	75	
2	98	93	89	96	92	88	93	90	86	91	88	85	82	
2.5	102	98	94	100	97	93	97	94	91	94	92	89	86	
3	105	101	98	103	100	97	100	97	95	97	94	92	89	
4	108	105	103	106	104	101	102	100	98	99	97	96	91	
5	110	108	105	108	106	104	104	102	100	100	99	97	93	

