


姿図



品 番	DDL-6002ABG
光 源	LED 5.8W 3500K
定格光束	390 lm
1/2照度角	62°
ビーム角	94°

器具効率	100.0 %
上方光束	0.0 %
下方光束	100.0 %
器具間隔 最大限 (取付高さH)	A 1.21 H B 1.21 H
保 守 率	良 0.67 中 0.63 否 0.56

反射率 (%)	天井	80			70			50			30			0
	壁	50	30	10	50	30	10	50	30	10	50	30	10	0
	床	20			20			20			20			0
室指数	照 明 率 (× 0.01)													
0.6	54	47	42	54	47	42	52	46	41	51	45	41	39	
0.8	65	57	52	64	57	52	63	56	51	61	55	51	49	
1	74	66	61	73	66	60	71	64	60	69	63	59	57	
1.25	81	74	69	80	74	69	78	72	68	76	71	67	64	
1.5	87	80	75	85	79	75	83	78	74	80	76	72	70	
2	95	89	85	93	88	84	90	86	82	87	84	81	77	
2.5	99	95	91	98	93	90	94	91	88	91	88	86	82	
3	103	99	95	101	97	94	97	94	91	94	92	89	85	
4	107	103	100	105	101	99	101	98	96	97	95	93	89	
5	109	106	103	107	104	102	103	100	98	99	97	95	91	

