


姿図



品番	LZD-9066FBB8_5000K
光源	LED 18.5W 6500K-2700K
定格光束	1690 lm
1/2照度角	40°
ビーム角	46°

器具効率	100.0 %
上方光束	0.0 %
下方光束	100.0 %
器具間隔 最大限 (取付高さH)	A 0.73 H B 0.73 H
保守率	良 0.67
	中 0.63
	否 0.56

反射率 (%)	天井	80			70			50			30			0
	壁	50	30	10	50	30	10	50	30	10	50	30	10	0
	床	20			20			20			20			0
室指数	照 明 率 ( × 0.01 )													
0.6	75	70	66	74	69	66	73	69	66	73	68	65	64	
0.8	82	77	73	81	76	73	80	76	72	79	75	72	70	
1	89	83	79	88	83	79	86	82	78	84	81	78	76	
1.25	94	89	85	93	88	85	91	87	84	89	85	83	80	
1.5	98	93	89	96	92	89	94	90	88	92	89	86	84	
2	103	100	96	102	98	95	99	96	94	96	94	92	89	
2.5	107	104	101	105	102	100	102	100	98	99	97	96	92	
3	110	107	105	108	105	103	104	102	101	101	100	98	95	
4	112	110	108	110	108	107	107	105	104	103	102	101	97	
5	114	112	111	112	110	109	108	107	106	104	103	102	98	

