


姿図



品番	DDL-5102WW
光源	LED 4.6W 5000K
定格光束	480.0 lm
1/2照度角	64°
ビーム角	92°

器具効率	100.0 %
上方光束	0.0 %
下方光束	100.0 %
器具間隔 最大限 (取付高さH)	A 1.26 H
	B 1.26 H
保守率	良 0.67
	中 0.63
	否 0.56

反射率 (%)	天井	80			70			50			30			0
	壁	50	30	10	50	30	10	50	30	10	50	30	10	0
	床	20			20			20			20			0
室指数	照 明 率 (× 0.01)													
0.6	56	49	44	56	49	44	54	48	44	53	48	43	42	
0.8	67	59	54	66	59	54	64	58	53	63	57	53	51	
1	75	68	63	74	67	62	72	66	62	70	65	61	59	
1.25	83	76	71	81	75	70	79	74	69	77	72	68	66	
1.5	88	82	77	87	81	76	84	79	75	82	77	74	71	
2	95	90	86	94	89	85	91	87	83	88	85	82	78	
2.5	100	95	92	98	94	91	95	92	88	92	89	87	83	
3	103	99	96	102	98	95	98	95	92	95	92	90	86	
4	107	104	101	105	102	99	101	99	96	98	96	94	89	
5	109	106	104	107	105	102	103	101	99	99	98	96	91	

