



| | |
|--------|---------------------|
| 品番 | LZW-93206YTW |
| 光源 | LED 10W 3000K |
| 定格光束 | 680 lm |
| 1/2照度角 | A-A' 80° B-B' 65° |
| ビーム角 | A-A' 252° B-B' 112° |

| | |
|------------------------|----------|
| 器具効率 | 100.0 % |
| 上方光束 | 29.6 % |
| 下方光束 | 70.4 % |
| 器具間隔 最大限 (取付高さH) | A 1.68 H |
| | B 1.27 H |
| 保守率 | 良 0.69 |
| | 中 0.67 |
| | 否 0.63 |

| 反射率 (%) | 天井 | 80 | | | 70 | | | 50 | | | 30 | | | 0 |
|---------|------------------|----|----|----|----|----|----|----|----|----|----|----|----|---|
| | 壁 | 50 | 30 | 10 | 50 | 30 | 10 | 50 | 30 | 10 | 50 | 30 | 10 | 0 |
| | 床 | 20 | | | 20 | | | 20 | | | 20 | | | 0 |
| 室指数 | 照 明 率 (× 0.01) | | | | | | | | | | | | | |
| 0.6 | 38 | 29 | 23 | 36 | 28 | 23 | 33 | 26 | 21 | 29 | 23 | 19 | 15 | |
| 0.8 | 47 | 38 | 31 | 45 | 36 | 30 | 40 | 33 | 28 | 36 | 30 | 25 | 20 | |
| 1 | 55 | 45 | 38 | 52 | 43 | 37 | 46 | 39 | 34 | 41 | 35 | 31 | 25 | |
| 1.25 | 62 | 53 | 45 | 59 | 50 | 44 | 53 | 45 | 40 | 47 | 41 | 36 | 29 | |
| 1.5 | 68 | 59 | 51 | 64 | 56 | 49 | 57 | 50 | 45 | 51 | 45 | 41 | 33 | |
| 2 | 76 | 68 | 61 | 72 | 65 | 58 | 64 | 58 | 53 | 57 | 52 | 48 | 39 | |
| 2.5 | 82 | 74 | 68 | 78 | 71 | 65 | 69 | 64 | 59 | 61 | 57 | 53 | 44 | |
| 3 | 86 | 79 | 73 | 82 | 75 | 70 | 73 | 68 | 63 | 65 | 61 | 57 | 47 | |
| 4 | 92 | 86 | 80 | 87 | 82 | 77 | 78 | 73 | 69 | 69 | 65 | 62 | 52 | |
| 5 | 96 | 90 | 86 | 90 | 86 | 81 | 81 | 77 | 73 | 72 | 69 | 66 | 55 | |

