

姿図



品 番	LLD-7061LUW+LZA-90635
光 源	LED 41W 2700K
定格光束	1050.0 lm
1/2照度角	31 °
ビーム角	32 °

器具効率	100.0 %
上方光束	0.0 %
下方光束	100.0 %
器具間隔 最大限 (取付高さH)	A 0.56 H B 0.56 H
保 守 率	良 0.67 中 0.63 否 0.56

反射率 (%)	天井	80			70			50			30			0
	壁	50	30	10	50	30	10	50	30	10	50	30	10	0
	床	20			20			20			20			0
室指数		照 明 率 (× 0.01)												
0.6		82	78	75	82	78	75	81	77	74	80	77	74	73
0.8		88	83	80	87	83	80	86	82	79	85	81	79	77
1		93	89	86	92	88	85	91	87	85	89	86	84	82
1.25		98	93	90	97	93	90	95	91	89	93	90	88	86
1.5		101	97	94	100	96	93	97	94	92	95	93	91	88
2		106	102	100	104	101	99	102	99	97	99	97	95	92
2.5		109	106	104	107	105	103	104	102	101	101	100	99	95
3		111	109	107	110	108	106	106	105	103	103	102	101	97
4		114	112	111	112	110	109	108	107	106	105	104	103	99
5		115	114	113	113	112	111	109	108	108	106	105	105	100

