


姿図



品番	LLD-7181AUWG
光源	LED 7.8W 3500K
定格光束	540 lm
1/2照度角	40°
ビーム角	48°

器具効率	100.0 %
上方光束	0.0 %
下方光束	100.0 %
器具間隔 最大限 (取付高さH)	A 0.73 H B
保守率	良 0.63
	中 0.60
	否 0.56

反射率 (%)	天井	80			70			50			30			0
	壁	50	30	10	50	30	10	50	30	10	50	30	10	0
	床	20			20			20			20			0
室指数	照 明 率 ( × 0.01 )													
0.6	79	74	71	79	74	71	78	74	71	77	73	70	69	
0.8	86	81	77	85	80	77	84	79	76	82	79	76	74	
1	91	87	83	91	86	83	89	85	82	87	84	81	80	
1.25	96	92	88	95	91	88	93	90	87	91	88	86	84	
1.5	100	95	92	98	95	92	96	93	90	94	91	89	86	
2	105	101	99	103	100	98	101	98	96	98	96	94	91	
2.5	108	105	103	107	104	102	104	102	100	101	99	98	94	
3	111	108	106	109	107	105	106	104	103	103	101	100	96	
4	113	111	110	111	110	108	108	106	105	104	103	102	98	
5	115	113	112	113	111	110	109	108	107	105	104	104	99	

