


姿図



品 番

LLC-7189XB+LZA-93519WBW

光 源

φ90 FLAT-LAMP 9W 5000K W

ランプ光束

1100 lm

1/2照度角

45°

ビーム角

49°

|      |        |
|------|--------|
| 器具効率 | 76.1 % |
| 上方光束 | 0.0 %  |
| 下方光束 | 76.1 % |

|                        |          |
|------------------------|----------|
| 器具間隔<br>最大限<br>(取付高さH) | A 0.82 H |
|                        | B 0.82 H |

|       |   |      |
|-------|---|------|
| 保 守 率 | 良 | 0.63 |
|       | 中 | 0.60 |
|       | 否 | 0.56 |

| 反射率<br>(%) | 天井 | 80               |    |    | 70 |    |    | 50 |    |    | 30 |    |    | 0  |
|------------|----|------------------|----|----|----|----|----|----|----|----|----|----|----|----|
|            | 壁  | 50               | 30 | 10 | 50 | 30 | 10 | 50 | 30 | 10 | 50 | 30 | 10 | 0  |
|            | 床  | 20               |    |    | 20 |    |    | 20 |    |    | 20 |    |    | 0  |
| 室指数        |    | 照 明 率 ( × 0.01 ) |    |    |    |    |    |    |    |    |    |    |    |    |
| 0.6        |    | 49               | 45 | 41 | 49 | 44 | 41 | 48 | 44 | 41 | 47 | 44 | 41 | 40 |
| 0.8        |    | 56               | 51 | 47 | 55 | 50 | 47 | 54 | 50 | 47 | 53 | 49 | 46 | 45 |
| 1          |    | 61               | 56 | 52 | 60 | 56 | 52 | 59 | 55 | 52 | 57 | 54 | 51 | 49 |
| 1.25       |    | 66               | 61 | 57 | 65 | 60 | 57 | 63 | 59 | 56 | 61 | 58 | 56 | 54 |
| 1.5        |    | 69               | 65 | 61 | 68 | 64 | 61 | 66 | 63 | 60 | 64 | 61 | 59 | 57 |
| 2          |    | 74               | 71 | 67 | 73 | 70 | 67 | 71 | 68 | 66 | 69 | 66 | 64 | 62 |
| 2.5        |    | 78               | 74 | 72 | 76 | 73 | 71 | 74 | 71 | 69 | 72 | 70 | 68 | 65 |
| 3          |    | 80               | 77 | 75 | 79 | 76 | 74 | 76 | 74 | 72 | 74 | 72 | 71 | 68 |
| 4          |    | 83               | 81 | 79 | 81 | 79 | 78 | 78 | 77 | 75 | 76 | 75 | 73 | 70 |
| 5          |    | 85               | 83 | 81 | 83 | 81 | 80 | 80 | 79 | 77 | 77 | 76 | 75 | 72 |

