


姿図



品 番	DSL-4458WW
光 源	LDA7N-G/60/5083 <DAIKO>
ランプ光束	860 lm
1/2照度角	64°
ビーム角	96°

器具効率	85.8 %
上方光束	24.5 %
下方光束	61.4 %
器具間隔 最大限 (取付高さH)	A 1.24 H B 1.24 H
保 守 率	良 0.67 中 0.63 否 0.56

反射率 (%)	天井	80			70			50			30			0
	壁	50	30	10	50	30	10	50	30	10	50	30	10	0
	床	20			20			20			20			0
室指数		照 明 率 (× 0.01)												
0.6		36	29	25	35	28	24	32	26	22	29	24	21	18
0.8		44	36	31	42	35	30	38	32	28	34	29	26	22
1		50	42	37	47	40	35	43	37	33	39	34	30	25
1.25		56	48	43	53	46	41	48	42	38	43	38	35	29
1.5		60	53	47	57	51	45	51	46	42	46	42	38	32
2		67	60	55	63	57	53	57	52	48	51	47	44	37
2.5		71	65	60	68	62	58	61	56	53	54	51	48	40
3		75	69	64	71	66	62	63	59	56	57	54	51	43
4		79	74	70	75	71	67	67	64	61	60	57	55	46
5		82	78	74	77	74	70	69	66	64	62	60	57	48

