


姿図



品 番	DDL-5003AB
光 源	LED 7.4W 3500K
定格光束	500.0 lm
1/2照度角	64°
ビーム角	92°

器具効率	100.0 %
上方光束	0.0 %
下方光束	100.0 %
器具間隔 最大限 (取付高さH)	A 1.24 H B 1.24 H
保 守 率	良 0.67 中 0.63 否 0.56

反射率 (%)	天井	80			70			50			30			0
	壁	50	30	10	50	30	10	50	30	10	50	30	10	0
	床	20			20			20			20			0
室指数		照 明 率 (× 0.01)												
0.6		56	49	44	55	49	44	54	48	43	53	47	43	41
0.8		67	59	54	66	59	54	64	58	53	63	57	53	51
1		75	68	62	74	67	62	72	66	61	70	65	61	59
1.25		82	76	70	81	75	70	79	73	69	77	72	68	66
1.5		88	81	76	86	81	76	84	79	75	81	77	74	71
2		95	90	86	94	89	85	91	87	83	88	85	82	78
2.5		100	95	91	98	94	90	95	91	88	92	89	86	83
3		103	99	96	101	98	95	98	95	92	95	92	90	86
4		107	104	101	105	102	99	101	99	96	98	96	94	89
5		109	106	104	107	104	102	103	101	99	99	98	96	91

