


姿図



品番	LZD-93551NBB+LZA-93015
光源	LED 30W 4000K
定格光束	2590 lm
1/2照度角	45°
ビーム角	49°

器具効率	100.0 %
上方光束	0.0 %
下方光束	100.0 %
器具間隔 最大限 (取付高さH)	A 0.83 H B 0.83 H
保守率	良 0.67
	中 0.63
	否 0.56

反射率 (%)	天井			壁			50			30			0		
	80	70	50	30	10	50	30	10	50	30	10	50	30	10	
室指数	照明率 (×0.01)														
0.6	83	79	76	83	79	76	82	78	76	81	78	75	74		
0.8	89	84	81	88	84	81	87	83	80	86	82	80	78		
1	94	90	87	93	89	86	92	88	85	90	87	85	83		
1.25	98	94	91	97	93	90	95	92	89	93	91	88	86		
1.5	101	97	94	100	97	94	98	95	92	96	93	91	89		
2	106	103	100	105	102	99	102	100	98	99	98	96	93		
2.5	109	107	105	108	105	103	105	103	101	102	100	99	96		
3	112	110	108	110	108	107	107	105	104	104	103	102	98		
4	114	113	111	112	111	110	109	107	107	105	104	104	99		
5	116	114	113	114	112	112	110	109	108	106	106	105	100		

