


姿図



品 番	DDL-8796AW
光 源	LED5.8W 3500K
定格光束	410.0 lm
1/2照度角	52°
ビーム角	68°

器具効率	100.0 %
上方光束	0.0 %
下方光束	100.0 %
器具間隔 最大限 (取付高さH)	A 0.97 H B 0.97 H
保 守 率	良 0.67 中 0.63 否 0.56

反射率 (%)	天井	80			70			50			30			0
	壁	50	30	10	50	30	10	50	30	10	50	30	10	0
	床	20			20			20			20			0
室指数		照 明 率 (× 0.01)												
0.6		62	56	51	62	55	51	61	55	51	60	54	51	49
0.8		71	65	60	71	64	60	69	63	59	68	63	59	57
1		79	72	68	78	72	67	76	71	67	74	70	66	64
1.25		86	79	75	84	79	74	82	77	73	80	76	72	70
1.5		91	85	80	89	84	80	87	82	78	84	80	77	74
2		98	93	88	96	91	88	93	89	86	90	87	84	81
2.5		102	98	94	100	96	93	97	94	91	94	91	89	85
3		105	101	98	103	100	97	100	97	94	96	94	92	88
4		108	105	103	106	104	101	103	100	98	99	97	96	91
5		111	108	106	108	106	104	104	102	101	101	99	98	93

