


姿図



品番	LZD-9089FWM8
光源	LED 24.8W 6500K-2200K
定格光束	1140 lm
1/2照度角	25°
ビーム角	26°

器具効率	100.0 %
上方光束	0.0 %
下方光束	100.0 %
器具間隔 最大限 (取付高さH)	A 0.44 H
	B 0.44 H
保守率	良 0.67
	中 0.63
	否 0.56

反射率 (%)	天井			壁			50			30			0		
	80	70	50	30	10	50	30	10	50	30	10	50	30	10	
床	20	20	20	20	20	20	20	20	20	20	20	20	20	20	
室指数	照 明 率 (× 0.01)														
0.6	84	80	77	84	80	77	83	79	76	82	79	76	75		
0.8	90	85	82	89	85	82	88	84	81	86	83	81	79		
1	95	91	87	94	90	87	92	89	86	91	88	86	84		
1.25	99	95	92	98	94	91	96	93	90	94	91	89	87		
1.5	102	98	95	101	97	95	99	96	93	96	94	92	90		
2	107	104	101	106	103	100	103	100	98	100	98	97	94		
2.5	110	108	105	109	106	104	106	104	102	103	101	100	97		
3	113	111	109	111	109	107	108	106	105	105	103	102	99		
4	115	113	112	113	112	110	109	108	107	106	105	104	100		
5	117	115	114	114	113	112	110	110	109	107	106	106	101		

