


姿図



品番	LZD-93566NBM+LZA-93015
光源	LED 32W 4000K
定格光束	2430 lm
1/2照度角	20°
ビーム角	20°

器具効率	100.0 %
上方光束	0.0 %
下方光束	100.0 %
器具間隔 最大限 (取付高さH)	A 0.35 H B 0.35 H
保守率	良 0.67
	中 0.63
	否 0.56

反射率 (%)	天井			壁			50			30			0		
	80	70	50	30	10	50	30	10	50	30	10	50	30	10	
床	20			20			20			20			0		
室指数	照 明 率 ( × 0.01 )														
0.6	84	79	76	83	79	76	82	78	76	81	78	75	74		
0.8	89	85	81	89	84	81	87	83	80	86	83	80	78		
1	95	90	87	94	89	86	92	88	86	90	87	85	83		
1.25	99	95	91	98	94	91	96	92	90	94	91	89	86		
1.5	102	98	95	101	97	94	98	95	93	96	94	92	89		
2	107	104	101	106	102	100	103	100	98	100	98	96	93		
2.5	110	108	105	109	106	104	106	104	102	103	101	100	96		
3	113	111	109	111	109	107	108	106	105	105	103	102	98		
4	115	114	112	113	112	110	110	108	107	106	105	104	100		
5	117	115	114	115	114	112	111	110	109	107	106	106	101		

