

姿図



品番	LZD-93533AWB+LZA-90822E
光源	LED 27W 3500K
定格光束	2250 lm
1/2照度角	50°
ビーム角	60°

器具効率	100.0 %
上方光束	0.0 %
下方光束	100.0 %
器具間隔 最大限 (取付高さH)	A 0.93 H B
保守率	良 0.67
	中 0.63
	否 0.56

反射率 (%)	天井	80			70			50			30			0
	壁	50	30	10	50	30	10	50	30	10	50	30	10	0
	床	20			20			20			20			0
室指数	照 明 率 (× 0.01)													
0.6	77	72	68	76	71	68	75	71	68	74	70	67	66	
0.8	84	78	75	83	78	74	81	77	74	80	76	73	72	
1	90	85	81	89	84	81	87	83	80	85	82	79	77	
1.25	95	90	86	94	89	86	92	88	85	90	86	84	82	
1.5	98	94	91	97	93	90	95	91	89	93	90	87	85	
2	104	100	97	102	99	96	100	97	95	97	95	93	90	
2.5	107	104	102	106	103	101	103	100	98	100	98	96	93	
3	110	107	105	108	106	104	105	103	101	102	100	99	95	
4	113	111	109	111	109	107	107	106	104	103	102	101	97	
5	114	113	111	112	111	109	108	107	106	104	104	103	98	

