



品番	DDL-6904AB
光源	LED 8.5W 3500K
定格光束	640 lm
1/2照度角	63°
1/2ビーム角	98°

器具効率	100.0 %
上方光束	0.0 %
下方光束	100.0 %
器具間隔 最大限 (取付高さH)	A 1.23H
保守率	良 0.67
	中 0.63
	否 0.56

反射率 (%)	天井 壁 床	80								70								50								30								20		0
		30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	10
室指数		照明率																																(×0.01)		
0.6		69	64	56	53	47	46	42	41	67	63	55	52	47	46	42	41	64	60	53	51	46	45	42	41	62	58	52	50	46	45	41	41	41	39	
0.8		80	73	67	63	59	56	53	51	78	72	66	62	58	56	52	51	74	69	64	61	57	55	52	51	71	67	62	60	56	55	51	51	51	49	
1		89	80	76	71	68	64	62	60	86	78	75	70	67	64	61	59	82	76	72	69	66	63	60	59	78	74	70	67	64	63	60	59	59	57	
1.25		96	86	85	78	77	72	71	67	94	84	83	77	76	72	70	67	89	82	80	75	74	71	69	67	84	79	77	74	72	70	67	66	66	64	
1.5		102	90	91	83	83	77	77	73	99	88	89	82	82	77	77	73	93	86	86	80	80	76	75	72	88	83	82	79	77	75	73	72	71	70	
2		109	95	100	90	93	85	88	81	106	94	98	89	92	85	87	81	100	91	93	87	88	83	84	80	94	89	89	85	85	82	82	79	79	77	
2.5		114	98	106	94	100	90	95	87	110	97	103	93	98	89	93	86	104	94	98	91	94	88	90	85	98	92	94	89	90	86	87	84	84	82	
3		117	100	110	96	105	93	100	90	113	99	107	95	102	92	98	90	106	96	102	94	98	91	94	89	100	94	97	92	94	90	91	88	87	85	
4		120	102	115	99	110	97	106	95	116	101	112	98	107	96	104	94	109	99	105	96	102	94	99	92	103	96	100	94	97	93	95	91	91	89	
5		122	104	118	101	114	99	110	97	118	102	114	100	111	98	107	96	111	100	108	98	105	96	102	95	104	98	102	96	100	95	98	93	93	91	
7		125	105	122	104	119	102	116	101	121	104	118	103	116	101	113	100	113	102	111	101	109	99	107	98	106	100	105	99	103	98	102	97	96	94	
10		127	107	125	105	123	104	121	103	123	105	121	104	119	103	117	102	115	103	113	102	112	101	110	101	107	101	106	100	105	100	104	99	98	96	

