


姿図



品 番	DSL-4898YB
光 源	LED 2700K 4W
定格光束	210.0 lm
1/2照度角	37°
ビーム角	40°

器具効率	100.0 %
上方光束	0.0 %
下方光束	100.0 %
器具間隔 最大限 (取付高さH)	A 0.66 H B 0.66 H
保 守 率	良 0.67 中 0.63 否 0.56

反射率 (%)	天井	80			70			50			30			0
	壁	50	30	10	50	30	10	50	30	10	50	30	10	0
	床	20			20			20			20			0
室指数		照 明 率 (× 0.01)												
0.6		80	76	73	80	75	72	79	75	72	78	74	72	71
0.8		86	81	78	85	81	77	84	80	77	83	79	77	75
1		91	87	83	91	86	83	89	85	82	87	84	82	80
1.25		96	91	88	95	91	87	93	89	86	91	88	85	83
1.5		99	95	92	98	94	91	96	92	90	93	91	88	86
2		104	101	98	103	100	97	100	97	95	97	95	93	90
2.5		108	105	102	106	103	101	103	101	99	100	98	97	93
3		110	108	106	108	106	104	105	103	102	102	101	99	96
4		113	111	109	111	109	108	107	106	105	104	103	102	98
5		114	113	112	112	111	110	108	107	107	105	104	103	99

