


姿図



品 番	DCL-40530A
光 源	LED 6W 3500K
定格光束	550.0 lm
1/2照度角	64°
ビーム角	110°

器具効率	100.0 %
上方光束	1.5 %
下方光束	98.5 %
器具間隔 最大限 (取付高さH)	A 1.26 H B 1.26 H
保 守 率	良 0.67 中 0.63 否 0.56

反射率 (%)	天井	80			70			50			30			0
	壁	50	30	10	50	30	10	50	30	10	50	30	10	0
	床	20			20			20			20			0
室指数		照 明 率 (× 0.01)												
0.6		46	38	32	46	38	32	44	37	32	43	36	32	30
0.8		56	48	41	55	47	41	54	46	41	52	45	40	38
1		65	56	49	63	55	49	61	54	48	59	53	48	45
1.25		72	64	57	71	63	57	68	61	56	66	60	55	52
1.5		78	70	64	77	69	63	74	67	62	71	65	61	58
2		87	80	74	85	79	73	82	76	71	79	74	70	66
2.5		93	86	81	91	85	80	87	82	78	83	79	76	72
3		97	91	86	95	89	85	91	86	83	87	83	80	76
4		102	97	93	99	95	91	95	92	89	91	88	86	81
5		105	101	97	102	99	96	98	95	92	94	91	89	84

