


姿図



品 番

DCL-39926A

光 源

LED 10.1W 3500K

定格光束

870.0 lm

1/2照度角

64°

ビーム角

106°

器具効率	100.0 %
上方光束	0.3 %
下方光束	99.7 %
器具間隔 最大限 (取付高さH)	A 1.24 H B 1.24 H
保 守 率	良 0.67 中 0.63 否 0.56

反射率 (%)	天井	80			70			50			30			0
	壁	50	30	10	50	30	10	50	30	10	50	30	10	0
	床	20			20			20			20			0
室指数		照 明 率 (× 0.01)												
0.6	47	39	33	47	39	33	45	38	33	44	38	33	31	
0.8	57	49	42	56	48	42	55	47	42	53	46	42	39	
1	65	57	50	64	56	50	62	55	50	60	54	49	46	
1.25	73	65	59	72	64	58	69	63	57	67	61	57	54	
1.5	79	71	65	78	70	64	75	69	63	72	67	62	59	
2	88	81	75	86	80	74	83	77	73	80	75	71	68	
2.5	93	87	82	91	86	81	88	83	79	85	81	77	73	
3	97	92	87	95	90	86	92	87	84	88	85	82	78	
4	102	98	94	100	96	92	96	93	90	92	90	87	83	
5	105	102	98	103	100	96	99	96	93	95	93	90	86	

