


姿図



品番	DCL-40530Y
光源	LED 6W 2700K
定格光束	520.0 lm
1/2照度角	64°
ビーム角	110°

器具効率	100.0 %
上方光束	1.5 %
下方光束	98.5 %
器具間隔 最大限 (取付高さH)	A 1.26 H B 1.26 H
保守率	良 0.67
	中 0.63
	否 0.56

反射率 (%)	天井	80			70			50			30			0
	壁	50	30	10	50	30	10	50	30	10	50	30	10	0
	床	20			20			20			20			0
室指数	照 明 率 (× 0.01)													
0.6	46	38	32	46	38	32	44	37	32	43	36	32	30	
0.8	56	48	41	55	47	41	54	46	41	52	45	40	38	
1	65	56	49	63	55	49	61	54	48	59	53	48	45	
1.25	72	64	57	71	63	57	68	61	56	66	60	55	52	
1.5	78	70	64	77	69	63	74	67	62	71	65	61	58	
2	87	80	74	85	79	73	82	76	71	79	74	70	66	
2.5	93	86	81	91	85	80	87	82	78	83	79	76	72	
3	97	91	86	95	89	85	91	86	83	87	83	80	76	
4	102	97	93	99	95	91	95	92	89	91	88	86	81	
5	105	101	97	102	99	96	98	95	92	94	91	89	84	

